

1200V/10A

SiC Schottky Barrier Diode

Characteristic


- Zero Reverse Recovery Current
- Positive temperature coefficient
- Temperature-independent performance
- High-speed switching
- Low switching loss
- Low heat dissipation requirements

Application

- Switching power supply
- Power factor correction
- Motor drive, traction
- Charging pile

Product Description

V_{RRM}	1200	V
$I_F(135^{\circ}C)$	17	A
Q_C	55	nC



Device	Package	Marking
SDS120J010D3	TO-252-2L	DS120010D3

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit	Test Conditions
Reverse voltage (Repetitive peak)	V_{RRM}	1200	V	$T_C=25^{\circ}C$
Reverse Voltage (Surge peak)	V_{RSM}	1200		$T_C=25^{\circ}C$
Reverse voltage (DC)	V_{DC}	1200		$T_C=25^{\circ}C$
Continuous forward current	I_F	37	A	$T_C=25^{\circ}C$
		17		$T_C=135^{\circ}C$
		10		$T_C=155^{\circ}C$
Surge non-repetitive forward current	I_{FSM}	103	A	$T_C=25^{\circ}C, t_p=10ms, half\ Sine\ Pulse$
Repetitive Peak Forward Surge Current	I_{FRM}	57	A	$T_C=25^{\circ}C, t_p=10ms, half\ Sine\ Wave\ D=0.1$
Total power dissipation	P_{TOT}	187	W	$T_C=25^{\circ}C$
i^2t value	$\int i^2 dt$	53	A^2s	$T_C=25^{\circ}C, t_p=10ms$
Operating temperature	T_j	-55~175	$^{\circ}C$	
storage temperature	T_{stg}	-55~175	$^{\circ}C$	

Thermal Characteristics

Parameter	Symbol	Values			Unit	Test Condition
		Min.	Typ.	Max.		
Thermal resistance	$R_{th(j-c)}$	/	0.80	/	$^{\circ}C/W$	

Electrical Characteristics $T_j=25^{\circ}C$

Parameter	Symbol	Values			Unit	Test Condition
		Min.	Typ.	Max.		
DC blocking voltage	V_{DC}	1200	/	/	V	$I_R=100\ \mu A$
Forward voltage	V_F	/	1.35	1.50	V	$I_F=10A, T_j=25^{\circ}C$
		/	1.85	2.20		$I_F=10A, T_j=175^{\circ}C$
Reverse current	I_R	/	2	30	μA	$V_R=1200V, T_j=25^{\circ}C$
		/	10	160		$V_R=1200V, T_j=175^{\circ}C$
Total capacitance	C	/	780	/	pF	$V_R=0V, f=1MHz$
		/	52	/		$V_R=400V, f=1MHz$
		/	38	/		$V_R=800V, f=1MHz$
Total capacitive charge	Q_C	/	55	/	nC	$V_R=800V$
Capacitance Stored Energy	E_C	/	15.8	/	μJ	$V_R=800V$

Typical Electrical Characteristics Curves




Figure 1. Forward Characteristics




Figure 2. Reverse Characteristics




Figure 3. Current Derating




Figure 4. Capacitance vs. Reverse Voltage




Figure 5. Power Derating




Figure 6. Capacitance Stored Energy





Figure 7. Total Capacitance Charge vs. Reverse Voltage

Package



SYMBOL	mm		
	MIN	NOM	MAX
A	2.2	2.3	2.38
A1	0	-	0.2
A2	0.97	1.07	1.17
b	0.68	0.78	0.9
b3	5.2	5.33	5.46
c	0.43	0.53	0.61
D	5.98	6.1	6.22
D1	5.30REF		
E	6.4	6.6	6.73
E1	4.63	-	-
e	2.286BSC		
H	9.4	10.1	10.5
L	1.38	1.5	1.75
L1	2.90REF		
L2	0.51BSC		
L3	0.88	-	1.28
L4	0.5	-	1
L5	1.65	1.8	1.95
θ	0°	-	8°

Ordering information

Part Number	SDS120J010D3-ISARH
Package	TO-252-2L
Unit Quantity	2500 EA
Packing Type	Tape Reel
RoHS	Yes